



## 212e, 232e, 242e E Style Keypads

### Flush Mount Backlit Keypad

- ❑ Single gang design
- ❑ Backlit hardened keys
- ❑ Sounder
- ❑ Weather Resistant
- ❑ UL 294 Access Control listed
- ❑ Five year warranty
- ❑ 212 style – 1 SPDT 2 amp relay
- ❑ 4.5" x 2.75" x 0.60"
- ❑ 10-30 VDC; 12-34 VAC – auto adjusting

**The 212 Series** keypads are designed for basic access control or code control for up to four individual devices (model dependent). These keypads are the perfect choice for controlling electric or magnetic locks, security systems, elevator control, gate controls, or other types of equipment requiring on/off or momentary control inputs.

### FEATURES

- ❑ 120 users
- ❑ Input trigger for Request to Exit or other open circuit contact
- ❑ Up to 4 independent outputs (model dependent)
- ❑ All outputs programmable for latched or timed operation.
- ❑ Keypad programmable

**The 232 Series** keypads are designed to meet most residential, commercial, and industrial single door access control requirements. Each 232 Keypad provides two inputs and four outputs, factory set access control.

### FEATURES

- ❑ 120 users
- ❑ Request to Exit input
- ❑ Door Monitoring input
- ❑ Relay outputs
  - Lock release
  - Door forced
  - Door propped
  - Alarm shunt
- ❑ Keypad programmable

**The 242 Series** combines the ease of the 232 Series with the flexibility of the 212 Series. It's four pre-programmed access control outputs can be reconfigured to operate in any combination by code.

### FEATURES

- ❑ 120 Users
- ❑ Request to Exit and Door Monitor inputs
- ❑ Four relay outputs independently assignable by code or a forced door; propped door; alarm shunt.
- ❑ Outputs programmable for latched or timed operation
- ❑ Keypad programmable